



SAFETY DATA SHEET
QUICK DRY WHITE SATIN PAINT

Page: 1

Compilation date: 27/02/2015

Revision date: 26/02/2018

Revision No: 4

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: QUICK DRY WHITE SATIN PAINT

Product code: WHISW

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.3. Details of the supplier of the safety data sheet

Company name: Rustins Ltd
Waterloo Road
Cricklewood
London
NW2 7TX
United Kingdom

Tel: +44 (0)208 450 4666

Fax: +44 (0)208 452 2008

Email: rustins@rustins.co.uk

1.4. Emergency telephone number

Emergency tel: .+44(0)2084504666 (Office hours only)

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CLP: Skin Irrit. 2: H315; Skin Sens. 1: H317; Eye Irrit. 2: H319; -: EUH208

Most important adverse effects: Contains texanol, a mixture of: 5-chloro-2-methyl-2h-isothiazol-3-one [ec no 247-500-7] and 2-methyl-2h-isothiazol-3-o. May produce an allergic reaction. Causes skin irritation.
May cause an allergic skin reaction. Causes serious eye irritation.

2.2. Label elements

Label elements:

Hazard statements: EUH208: Contains texanol, a mixture of: 5-chloro-2-methyl-2h-isothiazol-3-one [ec no 247-500-7] and 2-methyl-2h-isothiazol-3-o. May produce an allergic reaction.

H315: Causes skin irritation.

H317: May cause an allergic skin reaction.

H319: Causes serious eye irritation.

Hazard pictograms: GHS07: Exclamation mark



[cont...]

SAFETY DATA SHEET
QUICK DRY WHITE SATIN PAINT

Page: 2

Signal words: Warning

Precautionary statements: P102: Keep out of reach of children.

P262: Do not get in eyes, on skin, or on clothing.

P280: Wear protective gloves and eye protection.

P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P302+352: IF ON SKIN: Wash with plenty of water/.

P332+313: If skin irritation occurs: Get medical advice/attention.

2.3. Other hazards

PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

2-(2-BUTOXYETHOXY)ETHANOL

EINECS	CAS	PBT / WEL	CLP Classification	Percent
203-961-6	112-34-5	-	Eye Irrit. 2: H319	3.820%

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash immediately with plenty of soap and water.

Eye contact: Bathe the eye with running water for 15 minutes. Consult a doctor.

Ingestion: Wash out mouth with water. Do not induce vomiting. Consult a doctor.

Inhalation: Move to fresh air in case of accidental inhalation of vapours.

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: There may be mild irritation at the site of contact.

Eye contact: There may be irritation and redness.

Ingestion: No data available.

Inhalation: No data available.

4.3. Indication of any immediate medical attention and special treatment needed

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Carbon dioxide. Dry chemical powder. Alcohol resistant foam. Water spray. Water fog.

[cont...]

SAFETY DATA SHEET
QUICK DRY WHITE SATIN PAINT

Page: 3

5.2. Special hazards arising from the substance or mixture

Exposure hazards: In combustion emits toxic fumes of carbon dioxide / carbon monoxide.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Mechanically ventilate the spillage area whilst avoiding the formation of explosive concentrations - see section 9 of SDS. Mark out the contaminated area with signs and prevent access to unauthorised personnel. Do not attempt to take action without suitable protective clothing - see section 8 of SDS. Refer to section 8 of SDS for personal protection details.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method. Wash the ground with an appropriate self-emulsifying solvent.

6.4. Reference to other sections

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Ensure there is exhaust ventilation of the area. Avoid direct contact with the substance. Earth any equipment used in handling. Smoking is forbidden. Use non-sparking tools.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area. Keep away from direct sunlight. Keep container tightly closed.

Suitable packaging: Glass. Coated steel.

7.3. Specific end use(s)

Section 8: Exposure controls/personal protection

8.1. Control parameters

[cont...]

SAFETY DATA SHEET
QUICK DRY WHITE SATIN PAINT

Page: 4

Hazardous ingredients:

2-(2-BUTOXYETHOXY)ETHANOL

Workplace exposure limits:

Respirable dust

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	67.5 mg/m ³	101.2 mg/m ³	-	-

DNEL/PNEC Values

DNEL / PNEC No data available.

8.2. Exposure controls

Engineering measures: Ensure there is sufficient ventilation of the area.

Respiratory protection: Self-contained breathing apparatus must be available in case of emergency.

Hand protection: Protective gloves.

Eye protection: Safety glasses with side-shields.

Skin protection: Protective clothing. PVC apron.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State: Liquid

Colour: White

Odour: Barely perceptible odour

Evaporation rate: No data available.

Oxidising: Non-oxidising (by EC criteria)

Solubility in water: Miscible

Also soluble in: Benzene. Most organic solvents.

Viscosity: Viscous

Boiling point/range°C: 100

Melting point/range°C: No data available.

Flammability limits %: lower: No data available.

upper: No data available.

Flash point°C: >93

Part.coeff. n-octanol/water: No data available.

Autoflammability°C: No data available.

Vapour pressure: No data available.

Relative density: 1.017-1.027 @ 20 C

pH: 7.5 - 8.0

VOC g/l: No data available.

9.2. Other information

Other information: No data available.

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

[cont...]

SAFETY DATA SHEET
QUICK DRY WHITE SATIN PAINT

Page: 5

10.2. Chemical stability

Chemical stability: Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

10.4. Conditions to avoid

Conditions to avoid: Heat.

10.5. Incompatible materials

Materials to avoid: Oxidising agents. Strong acids.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes of carbon dioxide / carbon monoxide.

Section 11: Toxicological information

11.1. Information on toxicological effects

Hazardous ingredients:

2-(2-BUTOXYETHOXY)ETHANOL

ORL	MUS	LD50	6050	mg/kg
ORL	RAT	LD50	4500	mg/kg

Relevant hazards for product:

Hazard	Route	Basis
Skin corrosion/irritation	DRM	Hazardous: calculated
Serious eye damage/irritation	OPT	Hazardous: calculated
Respiratory/skin sensitisation	DRM	Hazardous: calculated

Symptoms / routes of exposure

Skin contact: There may be mild irritation at the site of contact.

Eye contact: There may be irritation and redness.

Ingestion: No data available.

Inhalation: No data available.

Section 12: Ecological information

12.1. Toxicity

Ecotoxicity values: No data available.

12.2. Persistence and degradability

Persistence and degradability: Biodegradable.

[cont...]

SAFETY DATA SHEET
QUICK DRY WHITE SATIN PAINT

Page: 6

12.3. Bioaccumulative potential

Bioaccumulative potential: No data available.

12.4. Mobility in soil

Mobility: Soluble in water. Volatile. Readily absorbed into soil.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Other adverse effects: No data available.

Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal company.

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

Section 14: Transport information

14.1. UN number

UN number: Not hazardous

14.2. UN proper shipping name

14.3. Transport hazard class(es)

14.4. Packing group

14.5. Environmental hazards

Environmentally hazardous: No

Marine pollutant: No

14.6. Special precautions for user

Special precautions: No special precautions.

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.2. Chemical Safety Assessment

Section 16: Other information

Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No 2015/830.

* indicates text in the SDS which has changed since the last revision.

[cont...]

SAFETY DATA SHEET
QUICK DRY WHITE SATIN PAINT

Page: 7

Phrases used in s.2 and s.3: EUH208: Contains <name of sensitising substance>. May produce an allergic reaction.
H315: Causes skin irritation.
H317: May cause an allergic skin reaction.
H319: Causes serious eye irritation.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.